




What a door!



The Detolux® system  
Overhead door for garages with  
restricted headroom clearance.

**Detolux** requires just 8 cm in the lintel headroom, although 17 cm provide the best installation conditions. This means that garages with restricted headroom clearance can be equipped with a top performance door system. The vertically opening and closing curtain glides parallel to the ceiling – smoothly and silently.

The head piece can be adjusted by up to 10% to suit the roof pitch. Besides the high-quality materials, the wear-free side locking with slide bearing soft rollers guarantees longevity and reliability.

The extensive range of standard equipment, from the radio-controlled motor to the automatic obstacle detection, offers you the greatest comfort and reliable safety. And the wide selection of colours and optional equipment allow you to create your own designs for that individual touch.





Detolux®



#### **Clever quality**

- Complete aluminium garage door
- No outward swing, allowing full use of space in front of the garage
- Made to measure
- Door made from single profiles
- Can be adjusted by up to 10% to suit the roof pitch
- Required lintel headroom can be reduced to just 8 cm
- Opening width of up to 400 cm
- 12 standard colours + 36 special Renolit colours
- TÜV tested, manufactured to DIN-EN standards

#### **Standard equipment**

- Remote control operation
- Motor with AÖS (opening protection)
- LLS (silent run system)
- Safety brake on both sides
- Ventilation profile
- Obstacle detection
- Integrated garage lighting
- Automatic courtesy light
- Concealed screw fixings in the guide rails
- Emergency unlocking from inside the garage
- Soft function for gentle door operation
- Endslat with 22 mm rubber hose

#### **Optional equipment**

- Emergency unlocking from the outside
- Solar or battery drive
- Vision profiles
- PIN code access
- Range of accessories for buttons and transmitters